



ALL TEMP

Mechanical Dish Detergent

PRODUCT USES

A heavy duty, chlorinated mechanical dishmachine detergent formulated for recirculating high temperature and low temperature dishmachines.

OPERATOR BENEFITS

- Removes stubborn food soils in soft to medium-hard water.
- Excellent results at an economical rack cost.
- Removes food soils and destains both china and plastic tableware.
- Rinses easily without filming.

DIRECTIONS FOR USE

For use in automated dispensing systems.

1. Carefully open the container to prevent spilling or splashing.
2. Insert the detergent pickup tube into the container opening.
3. The detergent is then dispensed automatically into the dishmachine.
4. Replace with new container when empty.

Not for manual use.
Do not use on aluminum.

PRODUCT SPECS

Pack size: 4/1 Gal., 5 Gal.

Characteristics: Non-viscous liquid

Rinsability: Excellent

Flammability: NA

Biodegradable: Yes

Color: Straw color

Odor: Nil

Foam: Non-foaming

pH in conc. form: 12.0 - 14.0

Phosphorous content: 1.5%

IMPORTANT OPERATOR INFORMATION

SDS:

Refer to the Safety Data Sheet (SDS) supplied by your distributor for information on emergency response, safe usage, hazards, first aid and proper product handling.

Emergency Response Phone: 1-800-424-9300

Statement of

Practical Treatment:

Product Precautions:

If swallowed: Dilute by giving large amounts of water or milk and call a physician.
For eye or skin contact: Flush with cool water for 15 minutes and call a physician.

DANGER: CORROSIVE

Harmful if swallowed. Causes severe burns to eyes and skin.

May be injurious to mucous membrane.

KEEP OUT OF REACH OF CHILDREN.

Shipping Classification:

UN1760, Corrosive Liquid, N.O.S., Class 8, PG II
(Contains Potassium Hydroxide, Sodium Hypochlorite)
CORROSIVE