

# SAFETY DATA SHEET



GT Cleaner

## Section 1. Identification

**GHS product identifier** : GT Cleaner  
**Other means of identification** : Not available.  
**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

**Supplier's details** : Betco Corporation  
400 Van Camp Road  
Bowling Green, Ohio 43402  
www.betco.com  
888-462-3826

**Emergency telephone number (with hours of operation)** : Chemtrec (800) 424-9300 24 hour

## Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3

### GHS label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : Flammable liquid and vapor.

### Precautionary statements

**Prevention** : Wear protective gloves: < 1 hour (breakthrough time): disposable vinyl. Wear eye or face protection: Recommended: safety glasses. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed.

**Response** : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Storage** : Store in a well-ventilated place. Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Other means of identification** : Not available.

### CAS number/other identifiers

**CAS number** : Not applicable.  
**Product code** : 695

| Ingredient name      | %        | CAS number |
|----------------------|----------|------------|
| 1-methoxy-2-propanol | ≥5 - <10 | 107-98-2   |
| Isopropyl alcohol    | ≥5 - <9  | 67-63-0    |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

## Section 4. First aid measures

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name      | Exposure limits   |
|----------------------|---|
| 1-methoxy-2-propanol | <b>ACGIH TLV (United States, 3/2015).</b><br>TWA: 50 ppm 8 hours.<br>TWA: 184 mg/m <sup>3</sup> 8 hours.<br>STEL: 100 ppm 15 minutes.<br>STEL: 369 mg/m <sup>3</sup> 15 minutes.<br><b>OSHA PEL 1989 (United States, 3/1989).</b><br>TWA: 100 ppm 8 hours.<br>TWA: 360 mg/m <sup>3</sup> 8 hours.<br>STEL: 150 ppm 15 minutes.<br>STEL: 540 mg/m <sup>3</sup> 15 minutes.<br><b>NIOSH REL (United States, 10/2013).</b><br>TWA: 100 ppm 10 hours.<br>TWA: 360 mg/m <sup>3</sup> 10 hours.<br>STEL: 150 ppm 15 minutes.<br>STEL: 540 mg/m <sup>3</sup> 15 minutes. |
| Isopropyl alcohol    | <b>ACGIH TLV (United States, 3/2016).</b><br>TWA: 200 ppm 8 hours.<br>STEL: 400 ppm 15 minutes.<br><b>OSHA PEL 1989 (United States, 3/1989).</b>  |

## Section 8. Exposure controls/personal protection

TWA: 400 ppm 8 hours.  
 TWA: 980 mg/m<sup>3</sup> 8 hours.  
 STEL: 500 ppm 15 minutes.  
 STEL: 1225 mg/m<sup>3</sup> 15 minutes.  
**NIOSH REL (United States, 10/2013).**  
 TWA: 400 ppm 10 hours.  
 TWA: 980 mg/m<sup>3</sup> 10 hours.  
 STEL: 500 ppm 15 minutes.  
 STEL: 1225 mg/m<sup>3</sup> 15 minutes.  
**OSHA PEL (United States, 6/2016).**  
 TWA: 400 ppm 8 hours.  
 TWA: 980 mg/m<sup>3</sup> 8 hours.

### Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses

#### Skin protection

##### Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): disposable vinyl

##### Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

##### Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Respiratory protection

- : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 8. Exposure controls/personal protection

Personal protective  
equipment (Pictograms)



## Section 9. Physical and chemical properties

### Appearance

|   |  |
|---|--|
| Physical state                                  | : Liquid.  |
| Color   | : Clear. Light blue-green.   |
| Odor  | : Ether-like.  |
| Odor threshold                                  | : Not available.   |
| pH  | : 7 to 10.5  |
| Melting point                                   | : Not available.   |
| Boiling point                                   | : Not available.   |
| Flash point                                     | : Closed cup: 38.333°C (101°F)   |
| Evaporation rate                                | : Not available.   |
| Flammability (solid, gas)                       | : Not available.   |
| Lower and upper explosive<br>(flammable) limits | : Not available.   |
| Vapor pressure                                  | : Not available.   |
| Vapor density                                   | : Not available.   |
| Relative density                                | : 0.966  |
| Solubility                                      | : Easily soluble in the following materials: cold water and hot water. |
| Partition coefficient: n-<br>octanol/water      | : Not available.   |
| Auto-ignition temperature                       | : Not available.   |
| Decomposition temperature                       | : Not available.   |
| Viscosity                                       | : Not available.   |

## Section 10. Stability and reactivity

|                                       |   |
|---------------------------------------|---|
| Reactivity                            | : No specific test data related to reactivity available for this product or its ingredients.  |
| Chemical stability                    | : The product is stable.  |
| Possibility of hazardous<br>reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| Conditions to avoid                   | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |
| Incompatible materials                | : Reactive or incompatible with the following materials:<br>oxidizing materials   |
| Hazardous decomposition<br>products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name | Result      | Species | Dose        | Exposure |
|-------------------------|-------------|---------|-------------|----------|
| 1-methoxy-2-propanol    | LD50 Dermal | Rabbit  | 13 g/kg     | -        |
|                         | LD50 Oral   | Rat     | 6600 mg/kg  | -        |
| Isopropyl alcohol       | LD50 Dermal | Rabbit  | 12800 mg/kg | -        |
|                         | LD50 Oral   | Rat     | 5000 mg/kg  | -        |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure                | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| 1-methoxy-2-propanol    | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams          | -           |
| Isopropyl alcohol       | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 10 milligrams           | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 100 milligrams          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams          | -           |

#### Sensitization

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Isopropyl alcohol       | -    | 3    | -   |

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

| Name                 | Category   | Route of exposure | Target organs    |
|----------------------|------------|-------------------|------------------|
| 1-methoxy-2-propanol | Category 3 | Not applicable.   | Narcotic effects |
| Isopropyl alcohol    | Category 3 | Not applicable.   | Narcotic effects |

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.



## Section 11. Toxicological information

**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route | ATE value     |
|-------|---------------|
| Oral  | 56747.2 mg/kg |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name | Result                               | Species                       | Exposure |
|-------------------------|--------------------------------------|-------------------------------|----------|
| Isopropyl alcohol       | Acute EC50 10100 mg/l Fresh water    | Daphnia - Daphnia magna       | 48 hours |
|                         | Acute LC50 1400000 µg/l Marine water | Crustaceans - Crangon crangon | 48 hours |
|                         | Acute LC50 4200000 µg/l Fresh water  | Fish - Rasbora heteromorpha   | 96 hours |

### Persistence and degradability

Not available.

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| 1-methoxy-2-propanol    | <1                 | -   | low       |
| Isopropyl alcohol       | 0.05               | -   | low       |



## Section 12. Ecological information

### Mobility in soil







**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                   | <b>DOT<br/>Classification</b>  | <b>TDG<br/>Classification</b>   | <b>Mexico<br/>Classification</b>   | <b>ADR/RID</b>  | <b>IMDG</b>  | <b>IATA</b>  |
|-----------------------------------|--|---|--|---|--|--|
| <b>UN number</b>                  | Not available.   | Not available.  | Not available.   | Not available.  | 1993   | Not available.   |
| <b>UN proper shipping name</b>    | Not Regulated For Ground Transportation.   | Not Regulated For Ground Transportation.  | Not Regulated For Ground Transportation.   | Not available.  | FLAMMABLE LIQUIDS, N.O. S. (Isopropanol, 1-methoxy-2-propanol)                             | Not available.   |
| <b>Transport hazard class(es)</b> | 3<br>   | 3<br>                                    | 3<br> | 3<br> | 3<br> | 3<br> |
| <b>Packing group</b>              | III  | III   | III  | III   | III  | III  |
| <b>Environmental hazards</b>      | No.  | No.   | No.  | No.   | No.  | No.  |
| <b>Additional information</b>     | This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). | -  | -   | (38.3° C c.c)  | -  |

## Section 14. Transport information

|  |            |  |  |  |  |  |
|--|------------|--|--|--|--|--|
|  | materials. |  |  |  |  |  |
|--|------------|--|--|--|--|--|

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
All components are listed or exempted.  
**Clean Water Act (CWA) 307:** disodium [29H,31H-phthalocyaninedisulphonato(4-)-N29, N30,N31,N32]cuprate(2-); copper  
**Clean Water Act (CWA) 311:** sodium hydroxide

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Fire hazard

#### Composition/information on ingredients

| Name                 | %        | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|----------------------|----------|-------------|----------------------------|----------|---------------------------------|---------------------------------|
| 1-methoxy-2-propanol | ≥5 - <10 | Yes.        | No.                        | No.      | Yes.                            | No.                             |
| Isopropyl alcohol    | ≥5 - <9  | Yes.        | No.                        | No.      | Yes.                            | No.                             |

### SARA 313

|  | Product name      | CAS number | %       |
|--|-------------------|------------|---------|
| <b>Form R - Reporting requirements</b> | Isopropyl alcohol | 67-63-0    | ≥5 - <9 |
| <b>Supplier notification</b>           | Isopropyl alcohol | 67-63-0    | ≥5 - <9 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

## Section 15. Regulatory information

- Massachusetts** : The following components are listed: PROPYLENE GLYCOL METHYL ETHER; PROPYLENE GLYCOL MONOMETHYL ETHER; ISOPROPYL ALCOHOL; 2-PROPANOL
- New York** : None of the components are listed.
- New Jersey** : The following components are listed: PROPYLENE GLYCOL MONOMETHYL ETHER; 1-METHOXY-2-PROPANOL; ISOPROPYL ALCOHOL; 2-PROPANOL
- Pennsylvania** : The following components are listed: 2-PROPANOL, 1-METHOXY-, Isopropanol

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### International lists

#### National inventory

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Europe** : Not determined.
- Japan** : **Japan inventory (ENCS)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.
- Malaysia** : Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | * | 2 |
| Flammability     |   | 2 |
| Physical hazards |   | 0 |
|                  |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)

## Section 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Procedure used to derive the classification

| Classification     | Justification         |
|--------------------|-----------------------|
| Flam. Liq. 3, H226 | On basis of test data |

### History

**Date of printing** : 4/24/2017

**Date of issue/Date of revision** : 2/9/2017

**Date of previous issue** : 12/6/2016

**Version** : 2.01

**Key to abbreviations** :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- UN = United Nations

**References** : Not available.

📌 Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.